

1600 IMP GALLON VACUUM TRUCK

TRUCK SPECIFICATIONS:

Chassis

- Freightliner, International, or Ford
- Diesel Engine 200-270 HP
- Automatic Transmission
- 160 Amp Alternator Hydraulic Brakes
- Fuel-water Separator
- Dual Batteries (Maintenance free)
 21,000 LB Single Speed Rear Axle
 Adjustable Oiler C/w Visual Glass
- 12,000 LB Front Axle & Front
- Stabilizer Bar
- 33,000 LB G.V.W.
- 50 Gallon Aluminum Fuel Tank
- 7" Monitor w/ Heated Shutter

- Heater, Defroster, and Air
- Conditioner
- 11R22.5 Radial Tubeless Tires

Septic Body/Plumbing

- 1600 IMP Gallon Vacuum Tank
- Spring Loaded Tank MountingFull Hose Trays/Fenders c/w
- Mud Flaps
 Removable Sight Glasses in Rear Tank Head
- Wallenstein 402H Vacuum Pump
- P.T.O Driven 190 FM Cap
- Adjustable Oiler c/w Visual Glass

- P.T.O Engage Inside Cab
- 2" Primary Floating Ball Check Valve
- Secondary Moisture Trap
- Heated Valve Cover at Secondary, Rear 3" Loading Valve and Rear 6" Dump Valve
 2 Lengths of 3"x 20' Soft Suction Hose
- c/w Camlock 24" Rear Door w/ Brass 6" Sliding Gate Style Dump Valve
- Pressure Vacuum Relief Valve
- One LED Spotlight installed at Pump • Two Standard Halogen Spot/Flood
- Lights at Rear
- D.O.T Running LightsNational Safety Mark Certified

Please contact the Fort Garry Fire Trucks sales department for more info. RR#2, 53 Bergen Cutoff Road, Winnipeg, MB R3C 2E6 PH: 1-800-565-3473 FAX: 1-204-694-3230 www.fgft.com

"Forged from Fire / Engineered for the Extreme"

*Photo for illustration purposes only.